

Valori PT-51 Second Display  
 11.6" LED, NON-TOUCH, BLACK W/PACKING



## LCM Specification

General	Display Method	LCD (Blue-White)
	Number of character	40 (20 columns × 2 lines) (Chinese 20*2)
	Brightness	600cd/m <sup>2</sup>
	Character font dot	8*16 dot matrix
	Panel dot	160*32 dot matrix
	Character type	95 Alphanumeric, 32 international characters
	Dot size (X×Y)	0.57mm(H) x 0.72mm(V)
	Active area	18.988(H) x 118.86(V)
	Module size	146 (L) × 45 (W) × 14 (H) mm
	Weight	Approx.72 grams
Commands Mode		LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support		FRANCE、GERMANY、U.K、DENMARKI、SWENEN、ITALY、SPAIN、JAPAN、NORWAY、DENMARKII、SLAVONIC、RUSSIA、Portuguese、Canadian French、Nordic、Turkish、Greek West European Latin.CP858、CP860、WCP1252、CP857 (TURKISH)、Polish、WPC1250、WPC1253 (GREEK)、WPC1255 (Hebrew)、WPC1251、CP866、CP852、CP737 (DOSgreek)、CP858、CP864 (Arabic) Farsi (Iran)、CP932(Japanese) 、CP936 (Simplified Chinese)、CP949 (Korean)、CP950 (Traditional Chinese)、PC862 (80H - FFH) 、PC775 : Baltic (80H-FFH) 、ISO8859-7 (80H -FFH)
Interface		RS-232 (serial) /USB Virtual COM
Reliability	MTBF	30000 hours
Power	Consumption	5V
EMC standards Safety standards		FCC, CE, ROHS