

## PT51 All-In-One Panel PC



### 15" PCAP Touchscreen

#### Features

- Support Intel 7th. Gen. CPU (Kabylake-U) and Celeron J1900 Processors
- 15" PCAP Touchscreen
- IP54 Water and Dust Resistant Front Panel
- VESA Mount Compliant
- 3 Track MSR, Customer display and 2nd display monitor Available

#### Applications

- Point of sale
- Self service
- Hospitality
- Restaurants
- Retail



## SPECIFICATIONS

	Motherboard	MA-36	MB-66	
<b>System</b>	Processor	Intel Bay Trail CPU Celeron J1900, up to 2.4GHz	Intel Kabylake-U Core i3-7020U	
	Graphic	CPU Intergrated		
	System Memory	1x DDR3L SO-DIMM up to 8GB	1x DDR4 SO-DIMM up to 16GB	
	Storage Device	1 x 64GB SSD (M.2)		
<b>LCD Touch Panel</b>	LCD Size	15" TFT LCD		
	Brightness	300 Units		
	Resolution	1024 x 768		
	Touch Screen	True-Flat PCAP Multi-touch		
<b>External I/O Ports</b>	USB	1 x USB 3.0, 7 x USB 2.0	4xUSB 3.0, 4x USB2.0	
	Serial Port	- COM1/2 (DB-9 RS232, support DC 0V/+5V/+12V by jumper setting, default setting is DC 0V) - COM3 is DB-9, standard COM port	- COM1/2 (DB-9 RS232 supports DC 0V/+5V/+12V, selectable by BIOS, default setting is DC 0V) - COM3 is DB-9, standard COM port	
	LAN	1 x RJ-45 (10/100/1000 baseT)		
	Cash Drawer	1x RJ11 (2 in 1)		
	VGA	1 x DB-15 (Support DC 0V/+12V by jumper setting. Default setting is DC +12v)	1x DB-15 (support DC 0V/+12V, selectable by BIOS, default setting is DC 0V)	
	DC Jack	1x DC+12V jack with locked Screw		
	Power Button	1		
	<b>Audio</b>	Internal Speaker	N/A	1 x 2w (Option)
	<b>Indicator</b>	LED Indicator	1 for Power LED	
	<b>Power</b>	Power Adapter	60W / DC+12V input	
<b>Peripheral (Option)</b>	MSR	3-Track MSR, USB Type		
	iButton	USB Type		
	Customer Display	LCM display 2 x 20 characters, USB Type		
	2nd Display	15.1" / 300 nits / 1024 x 768, VGA Type 11.6" / 250 nits / 1366 x 768, VGA Type		
	RFID	USB Type		
	Fingerprint			
<b>Mounting (Option)</b>	VESA Mount 75 x 75 / 100 x 100			
<b>Certificate</b>	EMC & Safety	CE/FCC		
<b>Environment</b>	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)		
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)		
	Humidity	20% ~ 80% RH non-condensing		
<b>Dimensions (WxDxH)</b>	360 x 199 x 330 mm			
<b>Weight</b>	5.01 kgs			
<b>OS Supported</b>	Windows 10			



**Tactile  
Technologies™**



## Get in touch

🏠 Cape Town  
☎ +27 21 914 0819

🏠 Johannesburg  
☎ +27 10 900 3991

🏠 Durban  
☎ +27 31 569 3488

✉ info.za@tactiletechnologies.com  
✉ service.za@tactiletechnologies.com  
✉ support.za@tactiletechnologies.com  
🌐 www.tactiletechnologies.com

🏠 Belgium  
☎ +32 478 786 623

✉ veronique@tactiletechnologies.com  
🌐 www.emea.tactiletechnologies.com



Visit Our Website

**The personal touch.**

