

Xprinter®

Impact Dot matrix Printer


XP-76IIN

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



XP-76IIN

Impact Dot matrix Printer



Model	XP-76IIN
Printing method	9-Pin serial impact dot-matrix printing
Printing width	63.5mm
Print Resolution	84 dpi
Printing speed	4.5 line/s Max.
Interface	Parallel / USB / USB+Lan
Print paper	75.5±0.5mm φ65mm
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese, traditional Chinese: 2.7×2.7mm (16×16 dots)
Column number	Font A - 33 columns /Font B - 40 columns / Chinese, traditional Chinese - 22 columns
Character	
Extension character sheet	PC437/Katakana/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858
Software	
Driver	Windows / Linux / Mac
Utility	Windows
SDK	Windows / Android
Power	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz, Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Physical characteristics	
Weight	1.46KG
Dimensions	230*150*138mm (D×W×H)
Environmental Requirements	
Work environment	0 ~ 45°C, 10 ~ 80% RH
Storage environment	-10 ~ 60°C, 10 ~ 90% RH (no condensation)
Reliability	
Printer head life	10 Million Lines



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

