EA520 Rugged Smartphone

IP67 & 1.5m Drop Protection I Removable 4250mAh Battery I Superior Barcode Reading (30 scans/sec)

Introducing the EA520, the 5" cutting-edge rugged smartphone delivers powerful barcode reading performance, convenient connectivity, durable but lightweight design that just fits in the palm of your hand. This enhance the service level for a variety of vertical applications within the retail, hospitality and field service sectors.

Portability for Better Retail Associate Experience

Powered by the Android 11 OS with GMS certification, the EA520 is equipped with octa-core CPU to deliver users excellent performance for smarter, more intuitive interactions. Specially designed for portability and versatile functionality, this device is easy to carry around for inventory checking, communicating with supervisor, supporting customers on the sales floor that redefines the retail associate working experience with convenient tool.

Powerful Barcode Reading Performance

Featuring powerful 1D/2D scanning capability, it also supports DPM codes and ensures read reliability for mobile phone screens and paper in any orientation. Powered by a removable 4250mAh battery, it is integrated HF/NFC RFID reader/writer, GPS, and a high-resolution 13MP camera in a compact device. The EA520 gives your workforce the technology it needs to take your business to the next level.

Durable at Its Best

The EA520 enhances the industrial durable protection with features including IP67 dustproof, waterproof and 1.5 meters resistant to fall protection (1.8 meters with boot case). That means it covers fully protected from dust and can survive in 1 meter of water for up to 30 mins.

Seamless And Connectivity

Featuring Bluetooth[®] 5, wireless dual bands with fast roaming and 4G connectivity for real-time data collection, staff can scans the item and instantly connect to the backend system to find out the quantity in stock or make an online order for customers. The EA520 delivers a seamlessly work experience and improves productivity for various applications.

Features

- 5-inch display with 450 nits sunlight readable
- Android 11 OS with GMS certification
- · Support 1D / 2D barcode on mobile screens, even DPM barcodes
- · Lightweight design that just fits in the palm of your hand
- All-In-One functionality: HF/NFC and 13MP camera
- Rugged: Corning[®] Gorilla[®] Glass 3 touch display, IP67 rated, and 1.5M drop (1.8M with boot case)
- Long-lasting removable 4250mAh battery
- Support Bluetooth® 5 / dual-band WLAN, fast roaming / 4G LTE
- · Support MDM Software Solutions and utilities such as MoboLink











System Features

OS	Android 11
GMS certified	GMS certified
CPU	Octa-core 2GHz Processor
Memory	4 GB RAM / 64 GB Flash
Languages support	Multiple languages
Others	Input Chinese/ English
	Supports handwriting and soft

Display

Screen Size Touchpanel

Keypad

Side SCAN button x 2 (Left / Right), User-defined function button (programmable key), volume up/down buttons, on/off button

Camera

8MP front camera 13M rear camera with LED flash and auto-focus function

Indicator Type

LED, Speaker, Vibrator

Symbologies

Support all major 1D and 2D barcodes

RFID

ΗF

Support HF/NFC, Frequency 13.56Mhz, ISO14443 A/B, ISO15693, Felica(ISO/IEC18092), Mifare compliance

keyboard

5.0" TFT-LCD HD (720 x 1280) color screen Gorilla Glass 3. Ultra sensitive capacitive touch screen,

compatible with gloves and supports wet resistance

Power Source Main Battery

3.85V 4250mAh Li-ion battery Removable

Software

SOTI, AirWatch, 42Gears, and MoboLink

Regulatory Approvals

CE, FCC, NCC, CCC, SRRC, VCCI, TELEC, RoHS, BQB, N-Mark, BSMI for battery



Headquarters

Taipei, Taiwan http://www.ute.com e-mail: info@hq.ute.com

unitech America Los Angeles

http://us.ute.com e-mail: info@us.ute.com http://can.ute.com info@can.ute.com Mexico http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei http://apac.ute.com info@apac.ute.com / info@india.ute.com http://mideast.ute.com info@mideast.ute.com

Communicatio	n
Blueteeth®	Bluetee

luetooth [®] 5 supported
02.11 a/b/g/n/ac/d/e/h/i/j/k/r/v, 2.4G+5GHz, support fast
paming, VoWiFi, hotspot,
ompliant with WFA, WPA/WPA2
lobal:
4G LTE FDD: B1/B2/B3/B5/B7/B8/B20/B28A/B28B
TDD: B38/B39/B40/B41
3G WCDMA: B1/B5/B8
2G GSM: 850,900,1800,1900MHz
mericas :
4G LTE FDD-B1/B2/B4/B5/B7/B12/B13/B14/B17/B28A/B28B
TDD-B38/B40/B41
3G WCDMA: B1/2/4/5/8
2G GSM: 850,900,1800,1900MHz
GPS, GPS, GLONASS, Beidou, Galileo
ght Proximity, Accelerometer, e-Compass, Gyroscope sensor
ptional

I/O Interfaces

USB	USB 2.0 (Type-C)
OTG	Yes, over USB Type-C
POGO PIN	Charging via cradle
SIM Slot	Dual SIM , support LTE + LTE
Expansion Slot	MicroSD, up to 256 GB
Audio	One speaker (1.5W / 95±3dB @ 10cm), One receiver,
	Dual noise-cancelling microphones

Enclosure

Weight

151.1mm x 76.8mm x 13.7mm 246g (with battery)

Environmental

Dimensions

Operating temperature	-20°C to 60°C
Storage temperature	- 40°C to 70°C (without battery)
Charging temperature	0°C to 45°C
Relative Humidity	95% (non-condensing)
Drop Specification	1.5m , 1.8m with boot case
Sealing	IP67
Vibration/ Tumble test	0.5m tumbles for 300 cycles / 600 drops

Accessories

- ■USB 2.0 type C cable
- 5V/2A Adaptor
- PE+ Adaptor Single Slot Charging Cradle
- Single Slot USB Cradle
- 4-Slot Terminal Charging Cradle
- 4-Slot Battery Charger

unitech Europe

Tilburg / Netherlands http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

Tokyo http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com



Specifications subject to change without notice. Copyright 2022 unitech Electronics Co., Ltd. All rights reserved. unitech is a registered trademark of unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.



Vehicle Cradle

EA520 Specifications



Development Tools



Device Management

SOTI

O H2GEARS

vmware[®]

Staging and Management

Productivity and Utilities



EA520



Android Enterprise ready EMM for monitoring device health and managing apps, configs and files.



StageGO Barcode-based device staging utility offering hundreds of script commands for you to work with.



OEMConfig If you are using a third party EMM, OEMConfig will allow those EMM solutions to configure unitech specific settings on the device.



Enterprise Launcher Secure your devices by kiosking them with Enterprise Launcher. Block access to the Android system and only allow limited number of apps to be run.



Battery info

Monitor advanced Battery health and manage the battery replacement cycle. Use with MoboLink to get real-time attery health alerts delivered to your phone.



Software Update

Check and install software updates online. To let a device always stay up-to-date, setup the device to automatically check and install for updates on boot up.



System Update Center

Check and install firmware updates via FOTA. You can update the firmware via online FOTA server, or by using a OTA ZIP file placed in the internal storage.



UNote A simple text viewer and editor for use in your work flows.



Startup Auto-run apps when device boots up.



KeyRemap Reprogram physical buttons to act as another key or to launch an app.



NTP Server Settings Customize the NTP server setting to keep your device date and time synchronized.

*All trademarks and registered trademarks are the property of their respective owners.