



# MOBILE PRINTER MP-A40 SERIES

## 4" Mobile Receipt and Label Printer

- 2 meters drop rate
- IP54 protection
- 105mm/s max printing speed
- -20°C to 50°C operating temperature
- Stylish design and simple operation
- Wide variety of driver and SDK for mobile equipment

# MP-A40 SERIES

## Mobile Printer



Measuring Instrument



PDA/Smart Device



Barcode



Portable Printer



Label



Medical Equipment

Made for

iPod iPhone iPad

MP-A40



Model		MP-A40
Printing	Method	Thermal line dot printing
	Number of dots/line	832
	Resolution (dots/mm)	203 (8 dots / mm)
	Paper width (mm)	80 <sup>0</sup> <sub>-1</sub> / 100 <sup>0</sup> <sub>-1</sub> / 105 <sup>0</sup> <sub>-1</sub> / 112 <sup>0</sup> <sub>-1</sub>
	Printing width (mm)	104
	Speed (mm/sec) max	105
	Outside diameter of paper roll (mm) max	Ø 58
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
Character dimensions (H×W mm)		3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of Paper		Roll paper, Label roll paper
Character type		Code page: 17pages, Katakana character, Option font, Downloaded character, User-dened character, JIS 1 & 2 level kanji
Bar code		UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
Power supply (V)		Option : specified AC adapter, Li-Ion battery
Communication interface		Communication interface USB, Bluetooth*
Input buffer		4k bytes
Command		ESC/POS™ conformity, CPCL conformity, Markup Language
Cutting		Tear bar
Drop rating		2.0m (6.6feet) multiple*2
IP rating		IP54*2
Operating temperature (°C)		-20 to 50
Service life (km)		50*3
Dimensions (W×D×H mm)		156 × 152 × 71*4
Mass (g)		Approx. 760*5
Standard		FCC, CE, VCCI
Included accessories		AC Adapter, AC cable, Battery pack, USB cable, Thermal paper sample roll
Optional accessories		Battery charger (single/quad), Serial cable, Car charger, Shoulder strap, Specified phenol free Thermal paper, Thermal labels (4x2", 4x3", 4x4", 4x6")
Software		Printer driver, Windows® CE(SDK), Android™(SDK), iOS

\*1 Selected model. \*2 test performance by specified condition. \*3 Use recommended thermal papers. \*4 Excluding protrusion \*5 Including battery, excluding roll paper

ESC/POS™: Registered trademark of SEIKO EPSON CORP.  
Windows® is the registered trademark of Microsoft Corporation(USA).

Android™ is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments GmbH

Siemensstraße 9, 63263 Neu-Isenburg, Germany  
phone: +49-6102-297-0 · e-mail: info@seiko-instruments.de  
www.seiko-instruments.de