




# MOBILE PRINTER MP-B30L SERIES

## 3" Mobile Label and Receipt Printer

- Ultra small & Lightweight
- 1,8m (6 feet) drop rate
- IP54 protection
- 130mm/s max print speed
- NFC for easy BT pairing
- BT or WiFi and USB interface
- Optional cradle for charging

# MP-B30L SERIES

## Mobile Printer



Measuring Instrument



PDA/Smart Device



Barcode



Portable Printer



Label



Medical Equipment

Made for

iPod iPhone iPad



**MP-B30L**  
Belt Clip



Model		MP-B30L
Printing	Method	Thermal line dot printing
	Number of dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	80 <sup>+0</sup> <sub>-1</sub> / 76.2 <sup>+0</sup> <sub>-1</sub> / 58 <sup>+0</sup> <sub>-1</sub>
	Printing width (mm)	72
	Printing Speed (mm/sec) max	130
	Outside diameter of paper roll (mm) max	Ø 51
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
	Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of Paper		Roll paper, Label roll paper
Character type		Code page(17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
Bar code		UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128,PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, AZTEC
Power supply		Li-ion Battery
Communication interface		USB, Bluetooth®, W-LAN <sup>*1</sup>
Input buffer		4K bytes
Command		ESC/POS™ conformity, ZPL II™ conformity, CPCL conformity
Cutting method		Tear bar
Falling resistance		1.8m <sup>*2</sup>
IP rating		IP54 <sup>*2</sup>
Operating temperature (°C)		-20 to 55
Service life: Abrasion resistance (km)		50 <sup>*3</sup>
Dimensions (W×D×H mm)		105 x 126 x 58 <sup>*4</sup>
Mass (g)		395 <sup>*5</sup>
Standard		FCC, CE, VCCI
Bundled item		AC adapter, Battery, USB cable, Belt clip
Option		Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap, Carrying case
Software		Printer driver, OPOS, POS for .NET, Windows® CE(SDK), Android™(SDK),iOS SDK, Xamarin SDK, URL Print Agent

<sup>\*1</sup> Selected model. <sup>\*2</sup> This number is test result based on SII procedures, not guaranteed value. <sup>\*3</sup> Use recommended thermal papers. <sup>\*4</sup> Excluding protrusion <sup>\*5</sup> with battery, without paper roll

ESC/POS™: Registered trademark of SEIKO EPSON CORP.  
Windows® is the registered trademark of Microsoft Corporation(USA).

Android™ is a trademark of Google Inc.  
IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



**Seiko Instruments GmbH**

Siemensstraße 9, 63263 Neu-Isenburg, Germany  
phone: +49-6102-297-0 · e-mail: info@seiko-instruments.de  
www.seiko-instruments.de