



**2D imager with adjustable stand**

Mounted on the wall, placed on a desk or adjusted angle with fixed position for hands-free scanning.



# MS339

## Affordable rugged 2D imager

**The Unitech MS339 is designed to meet barcode scanning needs at an affordable price.**

Supporting all common 1D and 2D barcodes, this high performance scanner is able to read poorly printed barcodes, reads damaged labels and reads digital barcodes from mobile displays (including QR codes) from various types of displays to enhance service levels.

The soft white auxiliary lighting and green aimer deliver comfortable and convenient scanning experience. The stylish and ergonomic design makes the MS339 fit comfortably in any hand, reducing fatigue during long-time scanning tasks.

**The MS339 comes all-in-one package including 5 years warranty!**

The MS339 is a great fit for a variety of retail and business environments. Its easy plug-and-play set up ensures an easy introduction into your unique workflow.

### Features

- The MS339 comes with coiled 2.4m USB-cable, hands-free stand and 5 years direct replacement warranty.
- Snappy performance.
- Decoding Rate 600 times per second
- Adjustable stand design - Desk mount, wall mount or adjustable hands-free scanning position.
- Supports USB/HID, USB/SPP, RS232 and OPOS.
- Reads poorly printed barcode and from mobile screens.
- Ergonomic design and comfortable grip.
- Supports Trigger and Auto-sensing mode.
- Durable design: 2.0 Meter drop test and IP52-rated.



# v1.6 MS339 Specifications

## Operational & Performance

Receiving Device	Imager sensor, 1280 x 800 pixels
Scan Skew	± 70°
Scan Pitch	± 75°
Scan Roll	360°
Motion Tolerance	1.5m/s.
Immunity:	100.000 lux
Light Source	Illumination: 5000K, white LED. Aiming: 525 nm peak wavelength, green LED.
Field of view	Horizontal 41° / Vertical 28°
Decoding Rate	600 times per second
Indicator	Beep, LED
Interface	USB/HID, USB/SPP, RS232 and OPOS* (additional software driver needed)

## Reading distance (DOF)

Depth of Field\*

1D: 0mm to 340mm	5mil Code39 (3 chars):	5 - 115
	10mil Code39 (3 chars):	0 - 250
	13mil UPC (6 chars):	15 - 340
	20mil Code39 (5 chars):	15 - 340
2D: 0mm to 340m	6.7mil PDF417 (20 chars):	10 - 100
	10mil QR (20 chars):	0 - 155
	10mil DM (20 chars):	0 - 160
	20mil QR (20 chars):	0 - 270

\* = dependents on width of barcode

## Symbologies

1D:

UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, Telepen, GS1 DataBar (formerly RSS) variants and TLC-39 postal code.

## Unitech Europe

Tilburg, The Netherlands  
 • Tel.: +31 (0)13 460 9292  
 • Email: [Info@eu.ute.com](mailto:Info@eu.ute.com)  
 • Website: <http://eu.ute.com>



Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan

\* Warranty: Unitech reserves the right to call back the defect units at her discrete sole decision if Unitech may find it necessarily. Upon the calling, the returning shipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop the warranty coverage before expiration if the defect is found due to abused, sabotage, and/or caused by the acts of God Specifications subject to change without notice.

Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

## 2D:

PDF417, QR Code, Data Matrix, Han Xin, Code, Aztec Code, MicroQR Code, MicroPDF417, **MaxiCode**.

## Power Source

Operation Voltage	5 VDC ± 0.25 V
Power consumption:	Standby: 1600 mA Working: 300 mA

## Material

Case material:	PC + TPU
Exit window material:	Tempered glass

## Enclosure

Scanner dimension	90mm x 62.8mm x 153mm
Scanner weight	132g (without cable)
Cable	2.4m coiled cable

## Environmental

Mechanical Shock	Withstands multiple 2.0m drops to concrete.
IP Rating	IP52
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 70°C
Relative Humidity	5% to 95% non-condensing

## Operation modes

Trigger, auto-sensing

## Connectivity

USB cable

## Safety & EMC

Photobiological Safety:	EN62471
EMC:	EN55032
ESD Protection:	EN61000-4-2
RF Immunity:	IEC61000-4-3, 10 V/m

## Regulator approvals

CE, FCC

## Warranty

5 Years scanner only\*  
 1 Year USB cable

**unitech**  
because we care